

HN-5RCS 5 Zone Remote Paging Station

- 5 zones high quality live paging
- Zone music on/off
- CHIME on/off
- Output level meter
- MIC volume control
- PTT and lock mode selectable
- Communication failure alert



HN-5RCS is specially designed for HN-series amplifier to provide remote control of zone on/off and live paging. Chime can be activated before paging. The robust industrial design enhances the product stability and the low-profile gray color can perfectly match with environment.

Connection Diagram



Technical Specifications

Parameter	Value
Power consumption	< 6 W
Frequency response	150 ~ 15kHz
Output sensitivity	+18 dBu (Adjustable)
Signal to noise ratio	> 75 dB (With A-Weight)
Non-linear distortion	< 0.5%
Indicator lights	1 power indicator 1 fault indicator 5 signal level indicators 5 zone on/off indicators 1 all on/off indicator 1 talk indicator
Operating conditions	95% humidity, 0°C ~+40°C (0~104°F) (no condensation)
Storage temperature	-10°C ~ +55°C (14°F~131°F)

Ordering Information

Description	Ordering Information
HN-5RCS 5 Zone Paging Station	HN-5RCS

HoneywellAudiovisuals

No. 257, Junye Road
Guangzhou GETDD East
510530 China

Tel: +86 20 2839 9600
Fax: +86 20 2820 8706
www.honeywellav.com

1010301056_EN1.3

Aug 2013

©2013 Honeywell International Inc.