

# Tiandy



TC-C32XN Spec: I3/E/Y/(M)/2.8mm

## 2MP Fixed IR Turret Camera



### KEY FEATURES

- Default: Metal+Plastic, M: Metal Housing
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. illumination Color: 0.02Lux@F2.0
- Smart IR, IR Range: 30m
- Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -35°~65°, 0~95% RH
- POE, IP67



**Tiandy Technologies Co.,Ltd.**

Email: [sales@tiandy.com](mailto:sales@tiandy.com) Tel: +86-22-58596178  
Website: [en.tiandy.com](http://en.tiandy.com) Fax: +86-22-58596048



## SPECIFICATIONS

| Camera                |  |
|-----------------------|--|
| Image Sensor          | 1/2.9" CMOS  |
| Signal System         | PAL/NTSC   |
| Min. Illumination     | Color: 0.02Lux@ (F2.0, ACG ON), B/W: 0Lux with IR  |
| Shutter Time          | 1s to 1/100,000s   |
| Day & Night           | Dual IR Cut Filter with Auto Switch  |
| Wide Dynamic Range    | Digital WDR  |
| Angle Adjustment      | pan 0~340°, tilt 0~75°, roate 0~360°   |
| Lens                  |  |
| Lens Type             | Fixed  |
| Focus                 | 2.8mm  |
| Lens Mount            | M12  |
| Aperture              | F2.0, Fixed  |
| FOV                   | Horizontal field of view: 97.4°  |
| Illuminator           |  |
| IR LEDs               | 2  |
| IR Range              | Up to 30m  |
| Wavelength            | 850nm  |
| White LEDs/Warmlights | N/A  |
| Compression Standard  |  |
| Video Compression     | S+265/H.265/H.264  |
| Video Bit Rate        | 32Kbps~6Mbps   |
| Audio Compression     | G.711/G.711U/ADPCM   |
| Audio Bit Rate        | 8K~48Kbps  |
| Image                 |  |
| Max. Resolution       | 1920x1080  |
| Main Stream           | PAL: 25fps (1920x1080, 1280x720, 704x576, 640x480)<br>NTSC: 30fps (1920x1080,1280x720, 704x480, 640x480) |
| Sub Stream            | PAL: 25fps (704x576, 704x288, 640x360, 352x288)<br>NTSC: 30fps (704x480, 704x240, 640x360, 352x240)      |
| Third Stream          | N/A  |
| Image Setting         | Saturation, brightness, contrast, sharpness, adjustable by client software or web browser                |
| Image Enhancement     | BLC/3D DNR/HLC   |
| ROI                   | N/A  |
| OSD                   | 16x16, 32x32, 48x48, adaptable size, Letters Such as Week, Date, Time, Total 3 Regions                   |
| Picture Overlay       | N/A  |
| Privacy Mask          | Yes, 4 regions   |
| Smart Defog           | Yes  |
| Feature               |  |
| Alarm Trigger         | Motion Detection, Mask Alarm, IP Address Conflict  |
| Video Analytics       | Tripwire, Perimeter  |
| Early Warning(EW)     | N/A  |



| Network                        |   |
|--------------------------------|---|
| <b>ANR</b>                     | Yes, auto store video in SD card when NVR disconnected, and upload video to NVR when resumed connection (Only Support Tiandy ANR NVR)                               |
| <b>Protocols</b>               | TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet   |
| <b>System Compatibility</b>    | ONVIF (PROFILE S/T/G), SDK, P2P(Mutually exclusive with Profile G)  |
| <b>Remote Connection</b>       | ≤7  |
| <b>Client</b>                  | Easy7, EasyLive   |
| <b>Web Version</b>             | Web5  |
| Interface                      |   |
| <b>Communication Interface</b> | 1 RJ45 10M/ 100M self adaptive Ethernet port  |
| <b>Audio I/O</b>               | Mic in  |
| <b>Alarm I/O</b>               | N/A   |
| <b>Reset Button</b>            | Yes   |
| <b>On-board storage</b>        | Built-in MicroSD card slot, up to 512 GB  |
| General                        |   |
| <b>Firmware Version</b>        | -   |
| <b>Web Client Language</b>     | 15 languages<br>English, Russian, Spanish, Korean, Italian, Turkish, Simple Chinese, Traditional Chinese, Thai, French, Polish, Dutch, Hebraism, Arabic, Vietnamese |
| <b>Operating Conditions</b>    | -35°C ~ 65°C, 0 ~ 95% RH  |
| <b>Power Supply</b>            | DC 12V±25%, PoE (802.3af)   |
| <b>Power Consumption</b>       | MAX: 6W (12V) MAX: 7W (PoE)   |
| <b>Protection</b>              | IP67, Lightning protection, surge protection and voltage transient protection meets EN 55035:2017   |
| <b>Heater</b>                  | N/A   |
| <b>Dimensions</b>              | Φ116.6×83.7mm (Φ4.59×3.30inch)  |
| <b>Weight</b>                  | Metal+Plastic: 0.34Kg (0.75lb) Metal: 0.47Kg (1.04lb)   |


\* Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at the same time.

## AVAILABLE MODEL

**TC-C32XN SPEC: I3/E/Y//2.8MM**

**TC-C32XN SPEC: I3/E/Y/M/2.8MM**

## DIMENSIONS



## ACCESSORIES



A29  
A29 WALL MOUNT



TC-P54BM SPEC: V5  
JUNCTION BOX



A36  
POLE MOUNT



A35  
CORNER MOUNT

DISTRIBUTED BY



**Tiandy Technologies Co.,Ltd.**

Email: [sales@tiandy.com](mailto:sales@tiandy.com)  
Website: [en.tiandy.com](http://en.tiandy.com)

Tel: +86-22-58596178  
Fax: +86-22-58596048